


ELECTRIX 202 SuperFlex

ELECTROTECHNICAL TAPES

TAPE STRUCTURE



PRODUCT DESCRIPTION

Backing:

- Plasticized PVC.

Adhesive:

- Rubber based adhesive.

Colour:

- Black, white, blue, red, yellow.

ELECTRIX 202 SuperFlex

Top quality PVC Electrical Tape.

APPLICATION

- Wrapping and waterproofing wire harnesses.
- Repairing damaged insulation.
- Isolation and bundling of wires.
- Strengthening the insulation in automotive electrical systems.
- Ideal for electrical, maintenance and color coding application.
- Excellent replacement for the combination of splicing and friction tape.

TECHNICAL DATA

Physical Properties	Unit	Value
Total thickness	mm	0.19
Breakdown voltage	kV	min. 7.6
Temperature range	°C	- 10 ÷ 85
Tensile strength	N/cm	min. 18
Adhesion to steel	N/cm	min. 1.8
Elongation	%	min. 100

FEATURES AND ADVANTAGES

- Highly flexible and elastic, perfectly adapts to the surface of irregular shapes and surfaces, easy to use.
- Frost resistant.
- Self-extinguishing.
- Weather resistance, including UV.
- Resistant to attrition, moisture and ageing.
- Excellent electrical insulation.

Product meets the applicable restrictions of RoHS Directive and Reach regulations, is VDE certified.



USAGE

- Apply to the dry, clean and degreased surface, free from other contaminants.
- Optimal application temperature: 10 ÷ 40°C.
- Wrap the tape with min. 50% overlap.
- During application use tension and pressure to smooth the tape by hand.

STORAGE

- To ensure the maximum product performance, store products in a dry, ventilated area in original packaging away from direct sunlight.
- Protect the products in original packaging against mechanical damage.
- The recommended storage temperature: -5 ÷ 40°C.

ANTICOR Sp. z o.o. holds ISO 9001.