


# Aluminio 374

## INDUSTRIAL TAPES

### TAPE STRUCTURE



### PRODUCT DESCRIPTION

**Backing:**

- A four-ply laminate structure (aluminium foil - 2 layers, poliester film - 2 layers).

**Adhesive:**

- Modified Acrylic system.

**Liner:**

- Silicone paper.

**Colour:**

- Silver.

### Aluminio 374

Universal, self-adhesive mechanical protection coating, vapor barrier, resistant to UV radiation.

A four-ply laminate structure.

### APPLICATION

- As a protective coat for anti-corrosion coatings of steel pipelines.
- As a protective sealing coating in heat and cold-insulating insulation used in external and internal installations in air-conditioning, ventilation, heating, refrigeration and others.
- An alternative to covers made of steel sheets and aluminum sheets.

### TECHNICAL DATA

Physical Properties	Jednostka	Wartość	Metoda testu
Total thickness	mm	0.145	ASTM D 3652
Backing thickness	mm	0.100	ASTM D 3652
Temperature range	°C	-35 ÷ 100	-
Adhesion to steel	N/cm	8.0	ASTM D 3330
Tensile strength	N/cm	120	ASTM D 3759
Elongation	%	25	ASTM D 3759

### FEATURES AND ADVENTAGES

- A four-ply laminate structure maintains high mechanical resistance to puncture and tearing.
- High resistance to weather conditions.
- Excellent UV and ozone resistance.
- 100% vapour barrier is guaranteed.
- Continuous working temperature: -30 ÷ 100°C.
- Lightweight and durable coating, fast and easy application.
- Available in rolls: length 50 m and the width 50, 100, 600 mm.

Product meets the applicable restrictions of RoHS Directive and Reach regulations.



ANTICOR Sp. z o.o. holds the ISO 9001:2015 certificate.

### USAGE

- Apply to the dry, clean, and degreased surface, free from other contaminants.
- Optimal application temperature: +10°C to +40°C.
- During application use tension and pressure to smooth the tape by hand or applicator.

### STORAGE

- Store the product in dry area in original packaging.
- Protect the cartons against mechanical damage.
- The recommended storage temperature: up to 25°C.