

SAFETY DATA SHEET
In accordance with Regulation (EU) 2020/878
ANTICOR Wrap Primer 729

Compilation date: 13.12.2013

Revision: 01.01.2023

Version: 5.0 ENG

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade name: **ANTICOR Wrap Primer 729**
Contains: n-butyl acetate, toluene, solvent naphta (petroleum), light arom.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Bituminous solvent primer for the building industry.

Uses advised against: not specified.

1.3. Details of the supplier of the safety data sheet

Supplier: ANTICOR Sp. z o.o.
Address: Wygoda 28, 32-020 Wieliczka, Poland
Telephone No/Fax No: +48 12 288 33 33 / +48 12 278 53 26
E-Mail: anticor@anticor.pl

1.4. Emergency telephone number

+48 12 288 33 33 (available from Monday till Friday during office hours: 8 am – 4 pm)
112 (24h)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification	According to Regulation (EC) no. 1272/2008
Hazard	
for physical-chemical properties:	Flam Liq. 2, H225 Highly flammable liquid and vapour.
for health hazards:	Repr. 2, H361d Suspected of damaging the unborn child. Asp. Tox. 1, H304 May be fatal if swallowed and enters airways. STOT RE 2, H373 May cause damage to organs through prolonged or repeated exposure. Eye Irrit. 2, H319 Causes serious eye irritation. Skin Irrit. 2, H315 Causes skin irritation. STOT SE 3, H336 May cause drowsiness or dizziness.
for environmental hazards:	Aquati Chronic 3, H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s): GHS02  GHS07  GHS08 

Signal word(s): Danger

Hazard statement(s):

H225 Highly flammable liquid and vapour.
H361d Suspected of damaging the unborn child.
H304 May be fatal if swallowed and enters airways.
H373 May cause damage to organs through prolonged or repeated exposure.
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.



SAFETY DATA SHEET
In accordance with Regulation (EU) 2020/878
ANTICOR Wrap Primer 729

Compilation date: 13.12.2013

Revision: 01.01.2023

Version: 5.0 ENG

Precautionary statement(s):

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/ eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P370+P378 In case of fire: Use dry chemical powder or carbon dioxide to extinguish.

Additional labeling:

VOC (Directive 2004/42/EC): Binding primers.

VOC given in g/litre of product in a ready-to-use condition: Limit value: 750 (2010)

VOC of product: 500,00

2.3. Other hazards

Not known.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Substance name	% mass	Product identifier	Regulation (EC) No 1272/2008 (CLP)	
			Hazard class	H-phrases
Xylene, mixture of isomers*	10 - 40	CAS nr: 1330-20-7 EC nr: 215-535-7 Index nr: 601-022-00-9 Registration nr: 01-2119488216-32-xxxx	Flam. Liq. 3 Acute Tox. 4 Acute Tox. 4 Skin Irrit. 2	H226 H312 H332 H315
Toluene*	10 - 20	CAS nr: 108-88-3 EC nr: 203-625-9 Index nr: 601-021-00-3 Registration nr: 01-2119471310-51-xxxx	Flam. Liq. 2 Repr. 2 Asp. Tox. 1 STOT RE 2 Skin Irrit. 2 STOT SE 3	H225 H361d H304 H373 H315 H336
n-Butyl acetate*	3 - 10	CAS nr: 123-86-4 EC nr: 204-658-1 Index nr: 607-025-00-1 Registration nr: 01-2119485493-29-xxxx		
Solvent naphta (petroleum), light arom.	3 - 10	CAS nr: Not applicable EC nr: 918-668-5 Index nr: Not applicable Registration nr: 01-2119455851-35-xxxx	Flam. Liq. 3 Asp. Tox. 1 STOT SE 3 STOT SE 3 Aquatic Chronic 2	H226 H304 H335 H336 H411 EUH066 Note P
Ethyl acetate*	3 - 10	CAS nr: 141-78-6 EC nr: 205-500-4 Index nr: 607-022-00-5 Registration nr: 01-2119475103-46-xxxx	Flam. Liq. 2 Eye Irrit. 2 STOT SE 3	H225 H319 H336 EUH066
Acetone*	1 - 3	CAS nr: 67-64-1 EC nr: 200-662-2 Index nr: 606-001-00-8 Registration nr: 01-2119471330-49-xxxx	Flam. Liq. 2 Eye Irrit. 2 STOT SE 3	H225 H319 H336 EUH066
Methyl ethyl ketone*	1 - 3	CAS nr: 78-93-3 EC nr: 201-159-0 Index nr: 606-002-00-3 Registration nr: Not available	Flam. Liq. 2 Eye Irrit. 2 STOT SE 3	H225 H319 H336 EUH066
Mesitylene	1 - 2.5	CAS nr: 108-67-8 EC nr: 203-604-4 Index nr: 601-025-00-5 Registration nr: Not available	Flam. Liq. 3 STOT SE 3 Aquatic Chronic 2	H226 H335 H411 STOT SE 3; H335: C ≥ 25%
Styrene*	1 - 3	CAS nr: 100-42-5 EC nr: 202-851-5 Index nr: 601-026-00-0 Registration nr: Not available	Flam. Liq. 3 Repr 2 Acute Tox. 4 STOT RE 1	H226 H361d H332 H372



SAFETY DATA SHEET
In accordance with Regulation (EU) 2020/878
ANTICOR Wrap Primer 729

Compilation date: 13.12.2013

Revision: 01.01.2023

Version: 5.0 ENG

			Eye Irrit. 2 Skin Irrit. 2	H319 H315
Ethylbenzene*	1 - 3	CAS nr: 100-41-4 EC nr: 202-849-4 Index nr: 601-023-00-4 Registration nr: Not available	Flam. Liq. 2 Acute Tox. 4 Asp. Tox. 1 STOT RE 2	H225 H332 H304 H373
4-Methylpentan-2-one*	0.1 - <1	CAS nr: 108-10-1 EC nr: 203-550-1 Index nr: 606-004-00-4 Registration nr: 01-2119473980-30-xxxx	Flam. Liq. 2 Acute Tox. 4 Eye Irrit. 2 STOT SE 3 Carc. 2	H225 H332 H319 H336 H351 EUH066 ATE inh = 11 mg/l (opary)
Heptane*	0.25 - 1	CAS nr: 142-82-5 EC nr: 205-563-8 Index nr: 601-008-00-2 Registration nr: 01-2119475515-33-xxxx	Flam. Liq. 2 Asp. Tox. 1 Skin Irrit. 2 STOT SE 3 Aquatic Acute 1 Aquatic Chronic 1	H225 H304 H315 H336 H400 (M=1) H410 (M=1)
n-Hexane*	0.1 - 1	CAS nr: 110-54-3 EC nr: 203-777-6 Index nr: 601-037-00-0 Registration nr: Not available	Flam. Liq. 2 Repr. 2 Asp. Tox. 1 STOT RE 2 Skin Irrit. 2 STOT SE 3 Aquatic Chronic 2	H225 H361f H304 H373 H315 H336 H411
1H-Imidazole-1-ethanol, 4,5-dihydro-, 2-nortall-oil alkyl derivs.	0.1 - 0.25	CAS nr: 61791-39-7 EC nr: 263-171-2 Index nr: Not applicable Registration nr: 01-2119931039-40-xxxx	Acute Tox. 4 Skin Corr. 1B Aquatic Acute 1 Aquatic Chronic 1	H302 H314 H400 (M=1) H410

* substance with exposure limits in the workplace

The product does not contain other substances presenting health or environmental hazard above the concentration limits given in the regulations.

The text of the H-phrases is shown in section 16 of the safety data sheet.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation:

Remove victim to fresh air. When any symptoms persists get medical attention.

Contact with skin:

Take off contaminated clothing and wash it before re-use. Wash skin thoroughly with soap and water, then flush with a plenty of water. Get medical attention immediately.

Contact with eyes:

Flush eyes with plenty of water for at least 15 minutes holding the eyelids open, remove contact lenses if present. Do not use neutralizing agents. When an irritation persists, consult an ophthalmologist.

Ingestion:

Get medical attention immediately. Do not induce vomiting. Do not give anything by mouth unless suggested by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: drowsiness, dizziness, slow reflexes, narcosis, CNS disorders, headache.

Contact with skin: irritation, redness, swelling, skin dryness and cracking.

Contact with eyes: irritation, redness, swelling, pain, tearing

Ingestion: even small quantities of this liquid absorbed via the respiratory system in case of ingestion or vomiting may cause bronchopneumonia and pulmonary oedema. Abdominal pain, nausea, vomiting.



SAFETY DATA SHEET
In accordance with Regulation (EU) 2020/878
ANTICOR Wrap Primer 729

Compilation date: 13.12.2013

Revision: 01.01.2023

Version: 5.0 ENG

4.3. Indication of any immediate medical attention and special treatment needed

As a general rule, in case of doubt or if symptoms persist, always call a doctor. Do not give anything to eat or drink to an unconscious person. Do not induce vomiting. Show the safety data sheet or label/ packaging to a person providing first aid.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media: foam, dry powder, carbon dioxide.

Unsuitable Extinguishing Media: water jets.

5.2. Special hazards arising from the substance or mixture

Excess pressure may be formed in containers exposed to fire - risk of explosion. Dangerous decomposition products may be formed during combustion - do not breathe vapours, it may be hazardous to your health.

5.3. Advice for firefighters

Cool containers with water spray and remove them into safe place. Prevent from entering contaminated water into sewers, rivers or other bodies of water. Dispose of waste water in compliance with current legislation. People should be properly trained and equipped with proper clothing and safety equipment. Use fire resistant protective clothing, breathing apparatus and eye protection.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unnecessary personnel. Do not inhale vapour/mist. Remove sources of ignition. Use adequate personal protective equipment as required in Section 8 of the safety data sheet.

6.2. Environmental precautions

Prevent from entering into drains, surface water and groundwater.

6.3. Methods and material for containment and cleaning up

Stop the leakage if possible. Cover spillage with an inert material eg. activated carbon, earth, sand, vermiculite, diatomite and then collect to a labelled container. Dispose of waste in compliance with current legislation.

6.4. Reference to other sections

Refer to Sections 8 and 13 of the safety data sheet.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Take precautions against electrostatic discharge and accumulation of vapours. Provide adequate ventilation. Handle uncleaned empty containers as full ones. Do not use compressed air during transport - explosion and fire hazard. Never eat, drink or smoke during use. Always wash hands with soap and water before and after work. Use adequate personal protective equipment as required in Section 8 of the safety data sheet.

7.2. Conditions for safe storage, including any incompatibilities

Store in cool area, in tightly closed, properly labelled, original containers. Keep away from heat sources, ignition sources, oxidizing agents.

7.3. Specific end use(s)

Not known.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters



SAFETY DATA SHEET

In accordance with Regulation (EU) 2020/878

ANTICOR Wrap Primer 729

Compilation date: 13.12.2013

Revision: 01.01.2023

Version: 5.0 ENG

Xylene, mixture of isomers (CAS 1330-20-7): PL: NDS: 100 mg/m³, NDSch: 200 mg/m³, NDSP: –, dermal
EU: 8h: 221 mg/m³, 50 ppm, 15 min: 442 mg/m³, 100 ppm
UK: 8h: 220 mg/m³, 50 ppm, 15 min: 441 mg/m³, 100 ppm

Toluene (CAS 108-88-3) PL: NDS: 100 mg/m³, NDSch: 200 mg/m³, NDSP: –, dermal
EU: 8h: 192 mg/m³, 50 ppm, 15 min: 384 mg/m³, 100 ppm
UK: 8h: 191 mg/m³, 50 ppm, 15 min: 384 mg/m³, 100 ppm

n-Butyl acetate (CAS 123-86-4) PL: NDS: 240 mg/m³, NDSch: 720 mg/m³, NDSP: –
EU: not applicable
UK: 8h: 724 mg/m³, 150 ppm, 15 min: 966 mg/m³, 200 ppm

Ethyl acetate (CAS 141-78-6) PL: NDS: 734 mg/m³, NDSch: 1468 mg/m³, NDSP: –
EU: not applicable
UK: 8h: 200 ppm, 15 min: 400 ppm

Acetone (CAS 67-64-1) PL: NDS: 600 mg/m³, NDSch: 1800 mg/m³, NDSP: –
EU: 8h: 1210 mg/m³, 500 ppm, 15 min: –
UK: 8h: 1210 mg/m³, 500 ppm, 15 min: 3620 mg/m³, 1500 ppm

Butan-2-one (CAS 78-93-3) PL: NDS: 450 mg/m³, NDSch: 900 mg/m³, NDSP: –, dermal
EU: 8h: 600 mg/m³, 200 ppm, 15 min: 900 mg/m³, 300 ppm
UK: 8h: 600 mg/m³, 200 ppm, 15 min: 899 mg/m³, 300 ppm

Styrene (CAS 100-42-5) PL: NDS: 50 mg/m³, NDSch: 100 mg/m³, NDSP: –
EU: not applicable
UK: 8h: 430 mg/m³, 100 ppm, 15 min: 1080 mg/m³, 250 ppm

Ethylbenzene (CAS 100-41-4): PL: NDS: 200 mg/m³, NDSch: 400 mg/m³, NDSP: –, dermal
EU: 8h: 442 mg/m³, 100 ppm, 15 min: 884 mg/m³, 200 ppm
UK: 8h: 441 mg/m³, 100 ppm, 15 min: 552 mg/m³, 125 ppm

4-Methylpentan-2-one (CAS 108-10-1) PL: NDS: 83 mg/m³, NDSch: 200 mg/m³, NDSP: –
EU: 8h: 83 mg/m³, 20 ppm, 15 min: 208 mg/m³, 50 ppm
UK: 8h: 208 mg/m³, 50 ppm, 15 min: 416 mg/m³, 100 ppm

Heptane (CAS 142-82-5) PL: NDS: 1200 mg/m³, NDSch: 2000 mg/m³, NDSP: –
EU: 8h: 2085 mg/m³, 500 ppm, 15 min: –
UK: 8h: 2085 mg/m³, 500 ppm, 15 min: –

Hexane (CAS 110-54-3) PL: NDS: 72 mg/m³, NDSch: –, NDSP: –, dermal
EU: 8h: 72 mg/m³, 20 ppm, 15 min: –
UK: 8h: 72 mg/m³, 20 ppm, 15 min: –

DNEL/PNEC: Not available

8.2. Exposure controls

Appropriate engineering controls:

Work under local exhaust/ventilation. Recommended eyewash facilities and safety showers.

Eye/face protection:

Protective glasses with side shields, goggles or face shield depending on application.

Skin protection:

Solvent resistant rubber gloves. Wear suitable protective clothing and boots.

Respiratory protection:

Gas mask with filter for organic vapours (A type) when exposure limits are exceeded.

Thermal hazards:

Not known.

Environmental exposure controls:

Precautions should be made against environmental contamination.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

- a) Physical state : Liquid
b) Colour : Black



SAFETY DATA SHEET
In accordance with Regulation (EU) 2020/878
ANTICOR Wrap Primer 729

Compilation date: 13.12.2013

Revision: 01.01.2023

Version: 5.0 ENG

c) Odour	: Not available
d) Melting point/freezing point	: Not available
e) Boiling point or initial boiling point and boiling range	: >80°C
f) Flammability	: Highly flammable liquid and vapour.
g) Lower and upper explosion limit	: Not available
h) Flash point	: <21°C
i) Auto-ignition temperature	: 245°C
j) Decomposition temperature	: Not available
k) pH	: Not applicable
l) Kinematic viscosity	: Not available
m) Solubility	: Insoluble in water
n) Partition coefficient n-octanol/water (log value)	: Not available
o) Vapour pressure	: Not available
p) Density and/or relative density	: 0.950 g/cm ³ ± 0.030 at 20°C
q) Relative vapour density	: Not available
r) Particle characteristics	: Not applicable

9.2. Other information

VOC content (directive 2004/42/CE)	: 50.75% - 481.94 g/l
VOC (volatile carbon)	: 41.42% - 393,49 g/l

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Mixture is not reactive.

10.2. Chemical stability

Mixture is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Avoid overheating. Avoid electrostatic discharges. Heat sources, ignition sources.

10.5. Incompatible materials

Strong oxidizing agents, acids.

10.6. Hazardous decomposition products

Not known. Hazardous combustion products are listed in Section 5 of the safety data sheet.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity:

Based on available data, the classification criteria are not met.

Solvent naphtha (petroleum), light arom.: LD50: 3492 mg/kg (oral, rat)

LD50: >3160 mg/kg (dermal, rabbit)

LC50: >6193 mg/l (4h, inhalation, rat)

1H-Imidazole-1-ethanol, 4,5-dihydro-, 2-nortall-oil alkyl derivs.: LD50: 947 mg/kg (oral, rat)

Xylene - mixture of isomers: LD50: 3523 mg/kg (oral, rat)

LD50: 4350 mg/kg (dermal, rabbit)

LC50: 26 mg/l (4h, inhalation, rat)

Toluene: LD50: 5580 mg/kg (oral, rat)

LD50: 12124 mg/kg (dermal, rabbit)



SAFETY DATA SHEET
In accordance with Regulation (EU) 2020/878
ANTICOR Wrap Primer 729

Compilation date: 13.12.2013

Revision: 01.01.2023

Version: 5.0 ENG

LC50: 28.1 mg/l (4h, inhalation, rat)
Ethylbenzene: LD50: 3500 mg/kg (oral, rat)
LD50: 15354 mg/kg (dermal, rabbit)
LC50: 17.2 mg/l (4h, inhalation, rat)
Mesitylene: LD50: 6000 mg/kg (oral, rat)
LD50L >2000 mg/kg (dermal, rat)
Styrene: LD50: 5000 mg/kg (oral, rat)
LC50: 11.8 mg/l (4h, inhalation, rat)
n-Hexane: LD50: 5000 mg/kg (oral, rat)
LD50: 3000 mg/kg (dermal, rabbit)
Methyl ethyl ketone LD50: 2737 mg/kg (oral, rat)
LD50: 6480 mg/kg (dermal, rabbit)
LC50: 23.5 mg/l (8h, inhalation, rat)
4-Methylpentan-2-one LD50: 2080 mg/kg (oral, rat)
LD50: >16000 mg/kg (dermal, rabbit)
LC50: >8.2 mg/l (4h, inhalation, rat)
n-Butyl acetate: LD50: >6400 mg/kg (oral, rat)
LD50: >5000 mg/kg (dermal, rabbit)
LC50: 21.1 mg/l (4h, inhalation, rat)

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Suspected of damaging the unborn child.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard:

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Data not available.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

Solvent naphta (petroleum), light arom.: LC50: 9.2 mg/l (96h, ryby)

EC50: 3.2 mg/l (48h, *Daphnia magna*)

1H-Imidazole-1-ethanol, 4,5-dihydro-, 2-nortall-oil alkyl derivs.: LC50: 0.63 mg/l (96h, ryby, *Oncorhynchus mykiss*)

Heptane: LC50: 375 mg/l (96h, ryby, *Tilapia mossambica*)

EC50: 82.5 mg/l (48h, *Daphnia magna*)

EC50: 1.5 mg/l (72h, glony, *Algae*)



SAFETY DATA SHEET
In accordance with Regulation (EU) 2020/878
ANTICOR Wrap Primer 729

Compilation date: 13.12.2013

Revision: 01.01.2023

Version: 5.0 ENG

Mesitylene: LC50: 12.52 mg/l (96h, ryby, *Carassius auratus*)

EC50: 6 mg/l (48h, *Daphnia magna*)

12.2. Persistence and degradability

Most of the mixture's components are readily biodegradable in water.

12.3. Bioaccumulative potential

Mixture: data not available.

12.4. Mobility in soil

Mixture: data not available.

12.5. Results of PBT and vPvB assessment

Mixture does not contain substances classified as PBT or vPvB in concentration above 0.1%.

12.6. Endocrine disrupting properties

Data not available.

12.7. Other adverse effects

Not known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Recycle or dispose of waste in compliance with current legislation. Remove to an authorised waste management company. Do not discharge into drains.

Packaging: Recycle or dispose of waste in compliance with current legislation.

Directive 2008/98/EC of the European Parliament and of the Council of the Member State.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number or ID number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

3

14.4. Packing group

II

14.5. Environmental hazards

No

14.6. Special precautions for user

Limited Quantities: 5L

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

Seveso - Directive 2012/18/WE: P5c

Annex XVII of REACH (restrictions): 3-40, toluene: 48

Annex XIV REACH (authorization)/Candidate List - SVHC: not applicable

15.2. Chemical safety assessment

Chemical safety assessment has not been carried out for the mixture- it is not required.



SAFETY DATA SHEET
In accordance with Regulation (EU) 2020/878
ANTICOR Wrap Primer 729

Compilation date: 13.12.2013

Revision: 01.01.2023

Version: 5.0 ENG

SECTION 16: OTHER INFORMATION

Classification method:

Classification is based on calculation method, information on the mixture's components and test results in accordance with criteria listed in CLP Regulation.

Changes made in the safety data sheet during revision:

Adaptation to Regulation EU 2020/878. Section 3, 8.1.

Legend to abbreviations and acronyms used in the safety data sheet:

NDS	Occupational Exposure Limit (Poland)
NDSch	Short-term Occupational Exposure Limit (Poland)
NDSP	Threshold limit value – ceiling (Poland)
OELs	Occupational Exposure Limits
vPvB	Very persistent and very bioaccumulative (substance)
PBT	Persistent, bioaccumulative and toxic (substance)
PNEC	Predicted No Effect Concentration
DNEL	Derived No Effect Levels
LD50	The dose of a tested substance causing 50% lethality during a specified time interval.
LC50	Concentration of a tested substance causing 50% lethality during a specified time interval
EC50	Concentration of a tested substance causing 50% changes in response (e.g. on growth) during a specified time interval

Literature references and sources for data:

Regulations/legislations mentioned in sections 2 – 15 of safety data sheet. Information supplied by the manufacturer (MSDS). ECHA database.

List of relevant hazard statements and/or precautionary statements, which are not written out in full under Sections 2 to 15:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Advice on any training appropriate for workers to ensure protection of human health and the environment:

Workers that use the product should be trained and informed about personal protection, accident procedure, etc.

Exposure scenarios: data is included in sections of the SDS.



SAFETY DATA SHEET

In accordance with Regulation (EU) 2020/878

ANTICOR Wrap Primer 729

Compilation date: 13.12.2013

Revision: 01.01.2023

Version: 5.0 ENG

Information in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. Information provided herein serves only as guidelines for safe work, use, processing, storage, and waste management. It cannot be considered as a warranty or quality certificate. This information applies only to specific material designated and may not be suitable for such material used in combination with any other materials or in any other manner not described in this document.

Prepared by **Mia-Che** www.mia-che.pl for ANTICOR Sp. z o.o.

