


# Polytex 111

## INDUSTRIAL TAPES

### TAPE STRUCTURE



### PRODUCT DESCRIPTION

#### Backing:

- Foil PE laminated cotton cloth.

#### Adhesive:

- Natural rubber.

#### Colour:

- Silver.

### Polytex 111

Professional duct tape for different applications.

### APPLICATION

- Holding, securing, seaming, repairing, bundling, splicing, packaging, masking and as moisture barrier.
- Joining and tightening thermal insulation.
- Tightening air-conditioning and ventilating ducts.

### FEATURES AND ADVANTAGES

- High tensile strength.
- Good adhesion.
- High tack.
- Waterproof.
- Good handling characteristics – does twist or curl during application. Well fits into irregular profiles and surfaces.
- No cutting tools necessary for application.

### USAGE

- Apply to the dry, clean, and degreased surface, free from other contaminants.
- Optimal application temperature: 10 ÷ 40°C.
- During application use tension and pressure to smooth the tape by hand.

### STORAGE

- Store the product in dry area in original packaging.
- Protect the cartons against mechanical damage.
- The recommended storage temperature: up to 25°C.

### TECHNICAL DATA

Physical Properties	Unit	Value
Total thickness	mm	0.23
Temperature range	°C	0 ÷ 93
Tensile strength	N/cm	min. 45.5
Adhesion to steel	N/cm	min. 6.02
Elongation	%	max 17

Product meets the applicable restrictions of RoHS Directive and Reach regulations.



ANTICOR Sp. z o.o. holds the ISO 9001:2015 certificate.