


### TAPE STRUCTURE



### PRODUCT DESCRIPTION

- Backing:**
- Plasticized PVC.
- Adhesive:**
- Synthetic rubber.
- Colour:**
- Gray.

### TECHNICAL DATA

Physical Properties	Unit	Value
Total thickness	mm	0.15
Dielectric strength	kV/mm	min. 40
Temperature range	°C	-10 ÷ 85
Tensile strength	N/cm	min. 13
Adhesion to steel	N/cm	min. 1.0
Elongation	%	min. 100

Product meets the applicable restrictions of RoHS Directive and Reach regulations.



ANTICOR Sp. z o.o. holds ISO 9001.

### 211

PVC adhesive installation Tape.

### APPLICATION

- Joining of cables in HVAC.
- Joining and sealing of pipes and channels of metal and plastics,
- Combining and fixing of typical insulation materials, particularly polyurethane foam PVC jacket.

### FEATURES AND ADVENTAGES

- Very good adhesion.
- Very flexible, convenient to use.
- Highly resistant to moisture, chemicals, aging.
- Frost resistant.
- Excellent electrical insulation.
- Wide temperature range of application

### USAGE

- Apply to the dry, clean and degreased surface, free from other contaminants.
- Optimal application temperature: 10 ÷ 40°C.
- Wrap the tape with min. 50% overlap.
- During application use tension and pressure to smooth the tape by hand.

### STORAGE

- To ensure the maximum product performance, store products in a dry, ventilated area in original packaging away from direct sunlight.
- Protect the products in original packaging against mechanical damage.
- The recommended storage temperature: -5 ÷ 40°C.