


540

INDUSTRIAL TAPES

TAPE STRUCTURE



PRODUCT DESCRIPTION

Backing:

- Nonwoven web.

Adhesive:

- Acrylic dispersion, solvent-free.

Liner:

- Siliconized PE-foil.

Kolor:

- White.

TECHNICAL DATA

Parameters	Unit	Value
Total thickness	mm	2, 3, 4, 5, 6
Density	kg/m ³	180 - 240
Fiber diameter	µm	3.2
Tensile strength	kPa	>350
Classification temperature (maximum service temperature)	°C	+1200
Melting point	°C	>1330
Thermal conductivity		
200°C	W/mK	0.07
400°C		0.10
600°C		0.15
800°C		0.22



ANTICOR Sp. z o.o. holds the ISO 9001 certificate.

ANTICOR 540

One sided self-adhesive, asbestos free high temperature glass fiber tape.

APPLICATION

- Sealing systems increased fire resistance.
- For high temperature insulation.
- In the construction industry as a seal carpentry and joinery in the highest class of fire resistance.

FEATURES AND ADVENTAGES

- Tape made from aluminosilicate fibers.
- High tensile strength.
- Resistant to high temperatures.
- Good adhesion.
- It has excellent thermal insulation properties.

USAGE

- Apply to the dry, clean and degreased surface, free from other contaminants.
- Optimal application temperature: 10÷40°C.
- During application use tension and pressure to smooth the tape by hand.

STORAGE

- To ensure the maximum product performance, store products in a dry, ventilated area in original packaging away from direct sunlight.
- Protect the products in original packaging against mechanical damage.
- The recommended storage temperature: -5 ÷ 40°C.