


ANTICORWrap 750-20

CORROSION PROTECTION

TAPE STRUCTURE



PRODUCT

DESCRIPTION

Backing:

- PE film.

Adhesive:

- Butyl-rubber.

Colour:

- Black, yellow.

ANTICORWrap 750-20

Mechanical protection tape (one-sided adhesive) in corrosion protection system C50 according to EN 12068.

APPLICATION

- In corrosion protection coatings of steel pipelines, steel tanks and fittings in underground and underwater buildings.

FEATURES & ADVENTAGES

- Excellent adhesion to the primered steel surface and on the overlap.
- Creates a uniform, compact coating.
- Compatible with most factory coatings.
- Minimal vapor permeability.
- High dielectric strength.

USAGE

- Condition the tape before application at 15÷30 °C.
- Wrap the tape around the surface spirally by hand or hand wrapping machine with tension causing 1-2% width reduction. (please see the detailed coating instruction before application).

STORAGE

- Store the product in dry area in original packaging.
- Protect the cartons against mechanical damage.
- The recommended storage temperature: up to 25°C.

PRODUCT FORM & SIZE AVAILABLE

50, 100 mm x 30 m, other sizes available on individual request.

TECHNICAL DATA

Parameters	Unit	Value	Test method
Thickness:			
• Total	mm	~ 0.50	-
• Backing	mm	~ 0.20	
• Adhesive	mm	~ 0.30	
Adhesion:		23°C 50°C	
tape/tape	N/cm	≥ 5 ≥ 2	EN 12068
Tensile strength	N/cm	≥ 100	EN 12068
Elongation	%	≥ 750	EN 12068
Water absorption	%	≤ 0.08	ASTM D 570
Hardness	Shore D	51	ISO 868
Operating temperature	°C	up to 50	EN 12068



ANTICOR Sp. z o.o. holds the ISO 9001:2015 certificate.

Copyrights © ANTICOR Sp. z o. o. All rights reserved

REV2-022021



www.anticor.pl