

ANTICORWrap Primer 720

CORROSION PROTECTION

STRUCTURE

Solids:

Butyl rubber and hydrocarbon resin

Solvent:

Petroleum spirit.

Colour: black.

TECHNICAL DATA

Parameters	Unit	Value
Solid parts	%	20
Density (in 20°C)	kg/dm ³	0.76
Flash point	°C	-12
Consumption	l/m ²	0.2



ANTICOR Sp. z o.o. holds the ISO 9001:2015 certificate.

ANTICORWrap Primer 720

Corrosion protection primer in class C and B steel surface protection systems, according to EN 12068.

RECOMMENDED USE / DESIGNED FOR

- Basic layer of corrosion protection in multi-layer tape systems, applied to the cleaned steel surface.
- Temporary corrosion protection of pipelines, steel tanks and fittings.

FEATURES AND ADVANTAGES

- Effectively protects steel surfaces against the effects of factors initiating corrosion processes.
- Contains Stress Corrosion Cracking inhibitors (SCC).
- Possess very good penetrating properties.
- Increases adhesion of coating to the protected steel surfaces.

APPLICATION

- Before applying the primer, condition the primer at the temperature above 15°C and mix thoroughly before use (do not dilute!).
- Apply the primer on prepared surface to the cleanliness degree Sa 2½ (according to ISO 8501).
In justified cases, it is allowed to prepare the surface to the degree of cleanliness St3 (mechanically, using steel rotating brushes).
- Apply a thin layer with a brush, brush, sponge, or spray. Do not use naked flames during application - primer and vapors are flammable!

STORAGE

- Store the product in dry area in original packaging.
- Protect the cartons against mechanical damage.
- The recommended storage temperature: up to 25°C.

PRODUCT FORM & SIZE AVAILABLE

Steel can: capacity 1 litre.